



How to determine the correct Ezi-action® M and C Adaptor Fittings

How can the correct M adaptor fitting for drums be determined?

Six different thread options cater for the many different thread styles from around the world. To determine the Ezi-action® adaptor fitting required for drums measure the outside diameter of the thread portion of the bung and describe the thickness of the thread.

Ezi-action® M fittings	Description
MBSP	55mm outside diameter with fine thread (Usual fitting on metal drums)
MBSP55	For a British standard fine thread (58mm outside diameter of bung) or a 56 x 4 buttress opening.
M55	55mm outside diameter with medium thread. Also known as Trisure, BCS, Mauser and coarse 56 x 4 buttress
M63	63mm outside diameter with coarse thread
M69	69mm outside diameter with coarse thread
MR	55mm outside diameter with fine thread (11 rings compared with the 10 rings on the MBSP)
M63B	63mm outside diameter with slightly coarser thread than M63
M63R	For a rieke fine thread (55mm outside diameter of bung) or into a drum with a coarse thread (63mm outside diameter of bung)



MR



M63

NZ Pump Company Ltd
21 Tawn Place
Hamilton 3200
New Zealand

Phone: +64 7 839 3838
Fax: +64 7 839 1193
E-Mail:
pacificsales@nzpump.com

New Zealand Pump Company Inc
801 South Palm Avenue,
Alhambra, CA 91803, USA

Phone: +1 626 458 8023
Fax :+ 1 626 458 8024
Email:
sales@nzpump.com

NZ Pump Company (Europe) Ltd
Unit 5/6 Greenline
Business Park
Wellington Street
Burton-on-Trent
Staffordshire DE14 2AS
UK

Phone: +44 (0) 1283 531499
Fax: +44 (0) 1283 531548
Email:
europesales@nzpump.com

How can the correct C adaptor fitting for containers be determined?

Nine different thread options including a Flexi Pour Spout Adaptor (PSA) cater for the many different thread styles from around the world. To determine the thread for containers measure the internal diameter of the container cap thread and describe the thickness of the thread and if necessary for further differentiation the shape of the thread.

Ezi-action® C fittings	Description
C55	55mm internal diameter with medium thread
C63Int	63mm internal diameter with medium thread and flat edge
C63 NZ	63mm internal diameter with medium thread and flat edge
Australian Metal	for metal containers 55mm internal diameter with fine/medium thread
C57 English	57mm internal diameter with coarse thread
English metal	56mm internal diameter with fine thread
C69 NZ	69mm internal diameter with coarse thread
C69 USA	69mm internal diameter with medium thread
Flexi Pour Spout Adaptor (PSA)	Replaces the flexi pour spout or can be inserted into a 71mm diameter hole cut into a container lid. (Instructions provided)
C65	65mm internal diameter with coarse thread



C69



PSA



The New Zealand Pump Company

Ezi-action®
DRUMPUMP

Preferred Locally
Demanded Globally